



Appn. No.: 10/002,763

Grp./A.U.: 3671

### Claim Amendments

**Claims 1-56** (canceled)

**Claim 57** (currently amended):

A picking rake for ~~collecting yard debris~~ performing raking and picking operations comprising:

a first and second rake units; and

the first rake unit having a first rake ~~head,~~ head and a first rake handle coupled to the first rake head; and

the second rake unit having a second rake ~~head,~~ head and a second rake handle coupled to the second rake head; and

each of the first and second rake ~~heads~~ units having an external side and an inner side; and

each of the first and second rake heads having a lower end and an upper end, wherein the lower ends of the first and second rake heads have a plurality of prongs forming a first plane; and

~~a first grip handle attached to the first rake handle, and a second grip handle attached to the second rake handle,~~ wherein the first rake handle includes a first hand grip and the second rake handle includes a second hand grip, wherein each of the first and second ~~grip handles~~ hand grips form a second plane substantially parallel to the first plane,

wherein the first and second ~~grip handles~~ hand grips and the first and second rake heads are facing toward each

other when the picking rake is used for picking up debris;  
and

wherein the first ~~grip handle~~ rake handle has a first portion and the second ~~grip handle~~ rake handle has a second portion, and one of the first and second portions has a first connecting means for holding the right and left rake units in a side by side relationship along their inner sides when the picking rake is used for raking yard debris; and portion; and

~~each of the first and second rake handles having lower and upper ends, wherein the lower ends are removably connected to the respective upper ends of the first and second rake heads, and wherein one of the upper ends of the first and second rake handles has an aperture through which a second connecting means is extended for flexibly and pivotally holding and connecting the first and second rake handles; and~~

connecting means on the rake units for keeping the rake heads together during the raking operation and apart during the picking operation; and

wherein the raking operation substantially comprises a conventional method of raking; and

wherein the longitudinal axes of the rake handles sweep a raking plane during the raking operation; and

wherein the connecting means comprise a gripping connection on one of the first and second portions; and

wherein the gripping connection operates along a gripping plane substantially normal to the raking plane for releasably holding and abutting the first and second rake units in a side-by-side relationship towards their inner sides during the raking operation; and

wherein at least one of the first and second ~~grip handles~~ are hand grips is located at a midsection of at least one of the first and second rake handles, and the first and second ~~grip handles~~ hand grips are located substantially remote from the upper ends of the first and second rake heads.

**Claim 58** (currently amended): The picking rake ~~for collecting yard debris~~ of claim 57, wherein the first and second rake heads have ~~a third~~ an additional connecting means for holding the first and second rake heads in a side by side relationship when the picking rake is used for raking yard debris.

**Claim 59** (currently amended): The picking rake ~~for collecting yard debris~~ of claim 57, wherein the ~~first connecting means~~ have gripping connection has an attaching means being secured to one of the first and second grip portions.

**Claim 60** (currently amended): The picking rake ~~for collecting yard debris~~ of claim 57

wherein the ~~first connecting means of gripping connection~~ on one of the first and second grip portions resiliently snaps onto and holds the other one of the first and second grip portions in an inwardly side-directed motion along the gripping plane before ~~when~~ the picking rake is used for raking yard ~~debris~~. debris; and

wherein the gripping connection on one of the first and second grip portions resiliently snaps off the other one of the first and second grip portions in an outwardly

side-directed motion along the gripping plane before the picking rake is used for picking debris.

**Claim 61** (withdrawn and currently amended): The picking rake ~~for collecting yard debris~~ of claim 57, wherein one of the first and second rake handles comprises at least two telescoping tubes, one receivable inside the other, and cooperating retaining means to telescope the tubes whereby the telescoping tubes can be extended when gathering debris and retracted when picking debris.

**Claims 62 - 77** (canceled)

**Claim 78** (canceled)

**Claim 79**(canceled)

**Claim 80** (canceled)

**Claim 81** (currently amended): A picking rake for ~~collecting yard debris~~ performing raking and picking operations comprising:

a first and second rake units; and

the first rake unit having a first rake head and a first rake handle; and

the second rake unit having a second rake head and a second rake handle; and

~~wherein each of the first and second rake heads has a first and second external side and a first and second inner side respectively; and~~

wherein each of the first and second rake heads has a lower end and an upper end; and

wherein the lower end of each of the rake heads has a plurality of prongs; and

wherein each rake handle comprise an elongated member having a lower end and an upper end; and

wherein the lower ends of the first and second rake handles are coupled to the upper ends of the first and second rake heads respectively; and

connecting means on the rake units for holding and connecting the rake units together comprising a pivotal connection for flexibly and pivotally connecting the upper end of one of the first and second rake handles to a section of the other of the first and second rake handles proximal the upper end of one of the first and second rake handles when the rake units are arranged in a raking position and a picking position; and

~~wherein the upper end of one of the first and second rake handles has part of a connecting means for flexibly and pivotally holding and fixedly connecting to the other one of the first and second rake handles; and~~

wherein the ~~connecting means~~ pivotal connection allows motion of the two rake handles in a cycle from a ~~first~~ the raking position to a ~~second~~ the picking position and back to the ~~first~~ raking position; and

wherein the ~~first~~ raking position comprise the rake handles substantially parallel and adjacent each other, ~~the inner sides of the rake heads next to~~ also adjacent each other, the lower ends of the rake heads aligned forming substantially one functional rake head lying on one plane, at least one rake head contributing to the total raking span ~~and substantially lying on the same plane~~; and

wherein the raking operation in the raking position comprise the conventional method of raking debris; and

wherein the motion leading to the ~~second~~ picking position comprise a ~~first~~ transition operation wherein at least one of the rake handles is separately flexed outwardly to turn about an azimuthal axis substantially parallel to the longitudinal axis of the rake handles, resulting in the ~~second~~ picking position wherein the rake heads are substantially facing each other; and

wherein a the picking operation in the ~~second~~ picking position comprises swinging at least one of the rake handles alternately inwardly toward and outwardly away from the other rake handle; and

wherein the motion leading back to the ~~first~~ raking position comprises the reverse of the first operation;  
transition operation.

~~whereby the first position is adapted for raking debris and the second position is adapted for grasping debris between the facing rake heads and for releasing the debris into a receptacle.~~

**Claim 82** (currently amended): The picking rake in claim 81 wherein the ~~connecting means~~ pivotal connection comprises the following or their equivalents:

- a) a first aperture on the upper end of one of the first and second rake handles, and
- b) a second aperture on the other rake handle disposed nearest the first aperture, and
- c) a cord, chain, or equivalent flexible elongated material, and
- d) wherein the flexible elongated material is threaded through the first and second apertures and closed off at each end with a retainer.

**Claim 83** (currently amended): The picking rake in claim 81 wherein the ~~connecting means~~ pivotal connection comprises the following or their equivalents:

- a) a chain comprising at least two links, said chain having a first link on one end and a last link on the other end, and
- b) wherein the first link is secured to the upper end of one of the first and second rake handles, and
- c) wherein the last link is secured to a section of the other of the first and second rake handles ~~elosest~~ proximal the first link.

**Claim 84** (currently amended): The picking rake in claim 81 wherein the ~~connecting mean~~ pivotal connection comprises the following or their equivalents:

- a) a first ring secured to the upper end of one of the first and second rake handles, and
- b) a second ring secured to a section of the other of the first and second rake handles ~~elosest~~ proximal the first ring, and
- c) means for turning at least one of the rings at least substantially 90 degrees freely around the orthogonal cross-sectional perimeter of the handle it is on, and
- d) wherein the first ring is linked to the second ring.

**Claim 85** (currently amended): The picking rake in claim 81 wherein the ~~connecting means~~ pivotal connection comprises the following or their equivalents:

- a) a first screw eye mounted on the upper end of one of the first and second rake handles, and

- b) a second screw eye mounted on the other of the first and second rake handles closest the first screw eye, and
- c) a first ring linking the first screw eye to the second screw eye.

**Claim 86** (currently amended): The picking rake in claim 81 wherein the ~~connecting means~~ pivotal connection comprises the following or their equivalents:

- a) a first aperture on one of the first and second rake handles, and
- b) a second aperture on the other of the first and second rake handles disposed closest to the first aperture, and
- c) a ring of size capable of being loosely threaded to the first and second apertures.

**Claim 87** (currently amended): The picking rake in claim 81 wherein each of the first and second rake heads has a first and second inner side respectively; and

wherein one of the first and second ~~the~~ inner sides overlap the other of the first and second inner sides, whereby the other of the first and second inner sides abuts the overlapping inner side of one of the first and second rake heads.

**Claim 88**(withdrawn and currently amended): A picking rake for ~~collecting yard debris~~ performing raking and picking operations comprising:

- a first and second rake units; and
- the first rake unit having a first rake head and a first rake handle ~~coupled to the first rake head;~~ and



the second rake unit having a second rake head and a second rake handle; and

wherein each of the first and second rake heads has an external side and an inner ~~side~~, side and

~~wherein each of the first and second rake heads has a~~ lower end and an upper end, wherein the lower ends of the first and second rake heads have a plurality of prongs; and

wherein each of the first and second rake handles has an external side and an inner side; and

wherein the first rake handle comprises a first elongated member and a first hand grip and the second rake handle comprises a second elongated member and a second hand grip; and

wherein each of the first and second elongated members has a lower end and an upper end; and

wherein the lower ends of the first and second elongated members are coupled to the upper ends of their respective rake heads; and

wherein the first and second hand grips each comprise a first branch extending substantially transversely outwardly from their respective elongated members at a section intermediate the upper ends of their respective rake heads and the upper ends of their respective elongated members; and

connecting means on at least one of the rake units for joining and abutting the two rake units towards the inner sides of the rake heads, the handles substantially parallel and next to each other, side-by-side along their inner sides on a first ~~infinite~~ plane, the lower ends of the rake heads aligned forming substantially one functional rake head also on the first ~~infinite~~ plane, at least one rake

head contributing to the total raking span when the picking rake is performing the raking operation; and

wherein the raking operation substantially comprises a conventional method of raking; and

wherein the elongated members sweep a raking plane during the raking operation; and

wherein said connecting means comprise a gripping connection comprising a resilient member disposed on one of the first and second rake handles; and

wherein the resilient member has an opening capable of receiving the outer dimensions of an adjacent section of the other of the first and second rake handles; and

wherein the resilient member is snapped onto the other of the first and second rake handles in an inwardly side-directed motion along a gripping plane substantially normal to the raking plane when the rake ~~units~~ heads are joined together for raking; and

wherein the resilient member is snapped off the other of the first and second rake handles in an outwardly side-directed motion along the gripping plane substantially normal to the raking plane when the rake ~~units~~ heads are ~~detached~~ parted for picking; and

~~wherein the first and second hand grips and the first and second rake heads are facing toward each other when the picking rake is used for picking up debris.~~

wherein the picking operation comprises the first and second hand grips and the first and second rake heads substantially facing each other and moving alternately toward and away from each other for grasping and releasing debris respectively between the first and second rake heads.

**Claim 89** (withdrawn): A picking rake in claim 88 further including abutment means to abut the two rake units together.

**Claim 90** (withdrawn): The picking rake in claim 89 wherein the abutment means comprise a recess disposed on a section of one of the rake handles, the recess sized to snugly receive the inner and outer dimensions of the resilient member.

**Claim 91** (withdrawn): The picking rake in claim 89 wherein the abutment means comprise overlapping rake heads.

**Claim 92** (withdrawn and currently amended): The picking rake in claim 88 further including ~~arm leveraging means.~~ a second branch extending substantially transversely from each of the elongated members at a section intermediate the upper end of the rake heads and the upper end of each of the elongated members and apart from the first branch, the first and second branches providing an arm leveraged handle during the picking operation.

**Claim 93** (withdrawn and currently amended): The picking rake in claim 88 wherein said ~~first connector~~ gripping connection further comprises:

- a) a first aperture on said resilient member,
- b) a second aperture disposed on a predetermined section of the other of the first and second rake handles,
- c) a snap button disposed inside the predetermined section of the other of the first and second rake handles, said snap button having a positioning

head, said positioning head outwardly engaged in the second aperture,

- d) wherein the resilient member snaps and holds other of the first and second rake handles, the positioning head further engaging outwardly into the first aperture when the two rake units are joined for raking debris, and
- e) wherein the snap button head is depressed inwardly to disengage from the first aperture when the two rake units are detached for picking debris.

**Claim 94** (withdrawn and currently amended): The picking rake in claim 88 ~~further including:~~

- ~~a) at least a third elongated member dimensionally receivable inside one of the first and second elongated members, and~~
  - ~~b) cooperating retaining means on the third member and on one of the first and second elongated members for telescoping the third elongated member in and out of one of the first and second elongated members, and~~
- ~~whereby the third elongated member is extended when raking and retracted when picking.~~

wherein one of the first and second elongated members comprises at least two tubes, an inner tube receivable inside an outer tube, and cooperating retaining means to telescope the tubes so that the inner tube can be extended when raking and retracted when picking debris.

**Claim 95** (withdrawn and currently amended): A picking rake for collecting yard debris comprising:

- a first and second rake units; and

the first rake unit having a first rake head and a first rake handle ~~coupled to the first rake head~~; and

the second rake unit having a second rake head and a second rake handle ~~coupled to the second rake head~~; and

wherein each of the first and second rake heads has an external side and an inner side; and

wherein each of the first and second rake heads has a lower end and an upper end, wherein the lower ends of the first and second rake heads have a plurality of prongs; and

wherein the first rake handle comprises a first elongated member and a first hand grip and the second rake handle comprises a second elongated member and a second hand grip; and

wherein each of the first and second elongated members ~~each~~ has a lower end and an upper end; and

wherein the lower ends of the first and second elongated members are coupled to the upper ends of their respective rake heads; and

wherein the first and second hand grips each comprise a first branch extending substantially transversely outwardly from their respective elongated members at a section intermediate the upper ends of their respective rake heads and the upper ends of their respective elongated members; and

connecting means on at least one of the rake units for joining the two rake units, the handles ~~substantially parallel and~~ next to each other, their longitudinal axes substantially parallel and distinct from each other, the lower ends of the rake heads aligned forming substantially one functional rake head, at least one rake head contributing to the total rake span when the picking rake is used for raking debris; and

wherein said connecting means comprise:

- a) a tube disposed along the elongated member of one of the first and second rake handles, said tube having a first aperture,
- b) a second aperture disposed on a predetermined section of the elongated member of the other of the first and second rake handles,
- c) ~~a snap button having a positioning head, said~~ snap button disposed inside the predetermined section of the elongated member of the other of the first and second rake handles, said snap button having a positioning head, the positioning head engaged outwardly of the second aperture,
- d) wherein the tube snugly receives the section of the elongated member of the other of the first and second rake handles when the section is inserted into the tube, the positioning head further engaging outwardly of the first aperture when the rake units are joined for raking debris, and
- e) wherein the snap button head is depressed inwardly from the first aperture while one of the rake handles is pulled out of the tube for picking debris, and

wherein the first and second hand grips and the first and second rake heads are facing toward each other when the picking rake is used for picking debris.

**Claim 96** (withdrawn): The picking rake in claim 95 further including abutment means comprising overlapping rake heads.

**Claim 97** (withdrawn and currently amended): The picking rake in claim 95 further including ~~arm leveraging means.~~ a second branch extending substantially transversely from each of the elongated members at a section intermediate the upper end of the rake head and the upper end of the elongated member and apart from the first branch, the first and second branches providing an arm leveraged handle during the picking operation.

**Claim 98** (withdrawn and currently amended): The picking rake in claim 95 ~~further including:~~

- ~~a) at least a third elongated member dimensionally receivable inside one of the first and second elongated members, and~~
- ~~b) cooperating retaining means on the third member and on one of the first and second elongated members, and~~

~~whereby the third elongated member is extended when raking and retracted when picking.~~

wherein one of the first and second elongated members comprises at least two tubes, an inner tube receivable inside an outer tube and cooperating retaining means to telescope the tubes whereby the inner tube can be extended when raking and retracted when picking debris.

**Claim 99** (withdrawn and currently amended): A picking rake for ~~collecting yard debris~~ performing raking and picking operations comprising:

- a first and second rake units; and
- the first rake unit having a first rake head and a first rake handle; and

the second rake unit having a second rake head and a second rake handle; and

~~wherein each of the first and second rake heads has a first and second external side and a first and second inner side respectively; and~~

wherein each of the first and second rake heads has a lower end and an upper end; and

wherein the lower end of each of the rake heads has a plurality of prongs; and

wherein each rake handle comprise an elongated member having a lower end and an upper end; and

wherein the lower ends of the first and second rake handles are coupled to the upper ends of the first and second rake heads respectively; and

connecting means on the rake units for holding and connecting the rake units together comprising a pivotal connection for flexibly and pivotally connecting the upper end of one of the first and second rake handles to a section of the other of the first and second rake handles proximal the upper end of one of the first and second rake handles when the rake units are arranged in a raking position and a picking position; and

~~wherein the upper end of one of the first and second rake handles has part of a connecting means for flexibly and pivotally holding and connecting to the other one of the first and second rake handles; and~~

wherein the connecting means pivotal connection is selected from a group consisting of the following or their equivalents:

A) ~~connecting means~~ the pivotal connection comprising:

- a. a first aperture on the upper end of one of the first and second rake handles, and



- b. a second aperture on the other rake handle disposed nearest the first aperture, and
  - c. a cord, chain or equivalent flexible elongated material, and
  - d. wherein the flexible elongated material is threaded through the first and second apertures and closed off at each end with a retainer; and
- B) ~~connecting means~~ the pivotal connection comprising:
- a. a chain comprising at least two links, said chain having a first link on one end and a last link on the other end, and
  - b. wherein the first link is secured to the upper end of one of the first and second rake handles, and
  - c. wherein the last link is secured to a section of the other of the first and second rake handles closest the first link; and
- C) ~~connecting means~~ the pivotal connection comprising:
- a. a first ring secured to the upper end of one of the first and second rake handles, and
  - b. a second ring secured to a section of the other of the first and second rake handles closest the first ring, and
  - c. means for turning at least one of the rings at least substantially 90 degrees freely around the orthogonal cross-sectional perimeter of the handle it is on, and
  - d. wherein the first ring is linked to the second ring; and
- D) ~~connecting means~~ the pivotal connection comprising:
- a. a first screw eye mounted on the upper end of one of the first and second rake handles, and

b. a second screw eye mounted on the other of the first and second rake handles closest the first screw eye, and

c. a first ring linking the first screw eye to the second screw eye; and

E) ~~connecting means~~ the pivotal connection comprising:

a. a first aperture on one of the first and second rake handles,

b. a second aperture on the other of the first and second rake handles disposed closest to the first aperture, and

c. a ring of size capable of being loosely threaded to the first and second apertures,

wherein the ~~connecting means~~ pivotal connection allows motion of the two rake handles in a cycle from ~~a first~~ the raking position to ~~a second~~ the picking position and back to the ~~first~~ raking position; and

wherein the ~~first~~ raking position comprise the rake handles substantially parallel and adjacent each other, ~~the inner sides of the rake heads next to~~ also adjacent each other, the lower ends of the rake heads aligned forming substantially one functional rake head lying on one plane, at least one rake head contributing to the total raking span and ~~substantially lying on the same plane~~; and

wherein the raking operation in the raking position comprise the conventional method of raking debris; and

wherein the motion leading to the ~~second~~ picking position comprise a ~~first~~ transition operation wherein at least one of the rake handles is separately flexed outwardly to turn about an azimuthal axis substantially parallel to the longitudinal axis of the rake handles,

resulting in the ~~second~~ picking position wherein the rake heads are substantially facing each other; and

wherein a the picking operation in the ~~second~~ picking position comprise swinging at least one of the rake handles alternately inwardly toward and outwardly away from the other rake handle; and

wherein the motion leading back to the ~~first~~ raking position comprise the reverse of the ~~first operation;~~ transition operation.

~~whereby the first position is adapted for raking debris and the second position is adapted for grasping debris between the facing rake heads and for releasing the debris into a receptacle.~~

Claims 100- 105(canceled)

Claim 106(new): The picking rake in claim 81

wherein the first rake handle has a first portion and the second rake handle has a second portion; and

wherein the connecting means further comprise a resilient member on one of the first and second portions for holding the first and second rake units in the raking position; and

wherein the resilient member is snapped off the other of the first and second portions at the start of the transition operation; and

wherein the resilient member is snapped onto the other of the first and second portions at the end of the reverse of the transition operation.

Claim 107(new): The picking rake in claim 81 wherein each of the first and second rake handles further includes a

hand grip comprising a branch extending substantially transversely outwardly therefrom.

Claim 108(new): The picking rake in claim 107

wherein the first hand grip has a first portion and the second hand grip has a second portion; and

wherein the connecting means further comprise a resilient member on one of the first and second portions for holding the first and second rake units in the raking position; and

wherein the resilient member is snapped off the other of the first and second portions at the start of the transition operation; and

wherein the resilient member is snapped onto the other of the first and second portions at the end of the reverse of the transition operation.

Claim 109(new): The picking rake in claim 81

wherein the other of the first and second rake handles comprises at least two tubes, an inner tube receivable inside an outer tube, and cooperating retaining means to telescope the tubes whereby the inner tube can be extended when gathering debris and retracted when picking debris.

Claim 110(new): The picking rake in claim 88

wherein said connecting means further comprise a pivotal connection for flexibly and pivotally holding and connecting the upper end of one of the first and second rake handles to a section of the other of the first and second rake proximal the upper end of one of the first and second rake handles.

Claim 111(new): A picking rake for performing raking and picking operations comprising:

a first and second rake units; and

the first rake unit having a first rake head and a first rake handle; and

the second rake unit having a second rake head and a second rake handle; and

wherein each of the first and second rake heads has an external side and an inner side, a lower end and an upper end, wherein the lower ends of the first and second rake heads have a plurality of prongs; and

wherein each of the first and second rake handles has an external side and an inner side; and

wherein the first rake handle comprises a first elongated member and a first hand grip and the second rake handle comprises a second elongated member and a second hand grip; and

wherein each of the first and second elongated members has a lower end and an upper end; and

wherein the lower ends of the first and second elongated members are coupled to the upper ends of their respective rake heads; and

wherein the first and second hand grips each comprise a first branch extending substantially transversely outwardly from their respective elongated members at a section intermediate the upper ends of their respective rake heads and the upper ends of their respective elongated members; and

connecting means on at least one of the rake units for joining the two rake heads together in a raking position and for parting the two rake heads in a picking position; and

wherein the raking position comprises the rake handles next to each other side-by-side along their inner sides, their longitudinal axes substantially parallel and distinct from each other, the rake heads adjacent each other towards their inner sides, their lower ends aligned forming substantially one functional rake head, at least one rake head contributing to the total raking span; and

wherein the picking position comprises the two rake heads substantially facing each other and the two hand grips substantially facing each other.

Claim 112(new): The picking rake in claim 111

wherein the raking operation substantially comprise a conventional method of raking; and

wherein the elongated members sweep a raking plane during the conventional method of raking; and

wherein the first hand grip has a first portion and the second hand grip has a second portion, said first and second portions substantially adjacent each other when the rake units are brought next to each other prior to being connected; and

wherein said connecting means comprise a gripping connection on one of the first and second portions comprising a resilient member that snaps onto and holds the other one of the first and second portions in an inwardly side directed motion along a gripping plane substantially normal to the raking plane when the picking rake is used for raking yard debris; and

wherein the resilient member snaps off the other of the first and second portions in an outwardly side directed motion along the gripping plane substantially normal to the

raking plane when the rake units are parted for picking yard debris.

Claim 113(new): The picking rake in claim 112 further including an aperture or equivalent securing means disposed on the upper end of one of the first and second rake handles through which a pivotal connection is extended for flexibly and pivotally holding and joining the first and second rake handles.

Claim 114(new): The picking rake in claim 112 further including a second branch extending substantially transversely from each of the elongated members at a section intermediate the upper end of the rake head and the upper end of the elongated member and apart from the first branch, the first and second branches providing an arm leveraged handle when the picking rake is used for picking debris.

Claim 115(new): The picking rake in claim 111 wherein the connecting means comprise:

- a) a tube disposed along the elongated member of one of the first and second rake handles, said tube having a first aperture,
- b) a second aperture disposed on a predetermined section of the elongated member of the other of the first and second rake handles,
- c) a snap button disposed inside the predetermined section of the elongated member of the other of the first and second rake handles, said snap button having a positioning head, the positioning head engaged outwardly of the second aperture,

- d) wherein the tube snugly receives the section of the elongated member of the other of the first and second rake handles when the section is inserted into the tube, the positioning head further engaging outwardly of the first aperture when the rake units are joined for raking debris, and
- e) wherein the snap button head is depressed inwardly from the first aperture while one of the rake handles is pulled out of the tube for picking debris.

Claim 116(new): The picking rake in claim 57 wherein the upper end of one of the first and second rake handles has an aperture or equivalent securing means through which a pivotal connection is extended for flexibly and pivotally holding and connecting the first and second rake handles.

Mary Ann Caneba  
(applicant) 6/23/04